



ORBITAL SANDERS

FEATURES

- VARIABLE SPEED CONTROL
- LOW VIBRATION
- REPLACEABLE PAD
- DURABLE AIR MOTOR
- PATENTS ON DESIGN
- MUFFLED EXHAUST

SPECIFICATIONS COMMON TO ALL MODELS

- AIR PRESSURE OF 90 PSI / 6.2 BAR
- PAD DIAMETER OF 6"
- WEIGHT OF 1.7 LB / 2 KG
- AIR CONSUMPTION OF 1.6 CFM
- FREE SPEED OF 11,000 RPM
- AIR INLET OF 1/4"



NON-VACUUM ASSIST



VACUUM ASSIST

MODEL NUMBER	DESCRIPTION
UPSANDER*	GENERAL PURPOSE SANDING, ORBIT DIA OF 5 MM, VACUUM ASSIST, H & L(1)
UPFSANDER*	FINE FINISH SANDING, ORBIT DIA OF 2.5 MM, VACUUM ASSIST, H & L(1)
UPSANDER-NV	GENERAL PURPOSE SANDING, ORBIT DIA OF 5 MM, NO VACUUM ASSIST, H & L (1)
UPFSANDER-NV	FINE FINISH SANDING, ORBIT DIA OF 2.5 MM, NO VACUUM ASSIST, H & L(1)
UPSANDER-AD	GENERAL PURPOSE SANDING, NO VACUUM ASSIST, ADHESIVE BACKING
UPFSANDER-AD	FINE SANDING, ORBIT DIA OF 2.5 MM, NO VACUUM ASSIST, ADHESIVE BACKING
(1) H & L	HOOK AND LOOP BACKING

* For use with a central vac system or portable vac system. See Uni-ram's portable vac UR700QVAC for 2 operators and the UR400QVAC for one operator at www.uniram.com.



Tel. 1-800-417-9133
 Fax 905-477-8922
sales@uniram.com

381 Bentley Street, Markham ON L3R 9T2
www.uniram.com