# PRESSURE SAND BLASTERS

dirt, rust, paint and other unwanted deposits

BLAST AWAY



The Sand Blaster abrasive penetrates into the deepest pitted area to remove rust. Readies the surface for priming.

Ideal for use in refinishing vehicles, boats, monuments, brick buildings and industrial equipment.

## **Common Features:**

- Portable
- Filling tank with abrasive is quick and easy
  - Comes with

Safety Shut - Off for operator safety

• Abrasive capacity about 100 lb

#### 35"

## Economical, U100-S

17"

**U100S** 

SABLEUSES A JET

 Complete with 8 ft, 4 ply, heavy duty hose

/

## U103-S

Complete with:

- 10 ft, 4 ply, heavy duty hose
- Moisture Filter
- Quick Disconnect Coupling for easy removal of hose from Sand Blaster

35"

Abrasive Control

Valve

Safety shut - off



# **Common Features of Portable Pressure Sand Blasters**



## Filling tank with abrasive is quick and easy:

- Pour abrasive with ease into Built In Funnel at top of tank.
- Return maintenance free filler plug and apply air pressure.

Abrasives include silica sand, glass beads, metal shot, aluminum oxide and nut shell.





Pressure Relief Valve / Air Inlet Shut - Off Valve Air Pressure Gauge Moisture Separator

## **Operation:**

- Open Air Inlet Shut Off Valve.
- Adjust Abrasive Control Valve.
- Squeeze Safety Shut Off to activate flow of abrasive.

The Safety Shut - Off is an innovative Uni-ram design. Releasing lever terminates abrasive flow for operator safety. Safety Shut - Off is also known as "Safety Blast Hand Control" or "Sgeezer Gun".

## AIR AND SAND CONSUMPTION BY NOZZLE SIZE

Part No.	Inside Diameter (in)	Compressor (HP)	CFM@80 PSI	Abrasive Consumption (Ib per hour)	Surface Blasting (sq ft per minute)
10-268	3/32	5	7	80 to100	0.5
10-260	1/8	5	20	150 to 170	1 to 1.5
10-264	5/32	5	30	200 to 210	1.5 to 2.0
10-261	3/16	5~10	45	300 to 350	3.0 to 3.5
10-262	1/4	5~10	80	500 to 600	4.0 to 4.5
10-265	5/16	10~15	125	800 to 950	6.0 to 7.0

Unit comes with three 1/8" diameter ceramic nozzles. Other available nozzles are shown in chart above.



#### CORPORATION

U.S.A.: 171 Cooper Ave., Ste. 108, Interstate Commerce Center, Tonawanda, NY 14150 Tel: (716) 874-8890 Fax: (716) 874-8893 Email: salesusa@uniram.com Canada: 381 Bentley Street, Markham, Ontario L3R 9T2 Tel: (905) 477-5911 Fax: (905) 477-8922 Website: www.uniram.com Email: salescan@uniram.com

U.S. Customers call: 1-800-735-4331 • Canadian Customers call: 1-800-417-9133

PRINTED IN CANADA

PATENT PENDING IN U.S.A., CANADA, AND OTHER COUNTRIES.

S. INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.